Click to prove you're human

The Dodge Dakota motor oil capacity can vary starting with 4.0 to 6.0 quarts hinging on the engine code, transmission type, year of manufacturing and the other features.Have a look at the charts listed here to grasp all the relevant peculiarities such as oil type, correct viscosity, oil change interval data both for standard as well as automatic transmissions. Tool Set Oil Filters Oil Filter Wrenches Air Filters Motor Oil 2011 2010 2009 2008 2007 2006 2005 2004 2003 2002 2001 2000 1999 Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-20 Coolant Capacity - 13.3 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-20 Coolant Capacity - 13.3 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-20 Coolant Capacity - 13.3 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-20 Coolant Capacity - 13.3 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 16.3 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 16.3 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 13.0 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft Chrysler / Chrysler LA engine / Magnum / 3.9L Magnum V6 Oil Capacity - 4.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 15.0 quarts Displacement - 3.9L V6 Horsepower - 180 HP Torque - 210 lb/ft Chrysler / Chrysler LA engine / Magnum / 5.9L Magnum V8 Oil Capacity - 5.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 15.0 quarts Displacement - 5.9L V8 Horsepower - 245 HP Torque - 335 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 17.0 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft American Motors Corporation / AMC straight-4 engine / AMC straight-4 engine / AMC 2.5L Oil Capacity - 4.5 quarts Oil Viscosity - 5W-30 Coolant Capacity - 10.0 quarts Displacement - 2.5L I-4 Horsepower - 120 HP Torque - 139 lb/ft Chrysler / Chrysler LA engine / Magnum / 3.9L Magnum V6 Oil Capacity - 4.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 13.7 quarts Displacement - 3.9L V6 Horsepower - 180 HP Torque - 210 lb/ft Chrysler / Chrysler LA engine / Magnum / 5.9L Magnum V8 Oil Capacity - 5.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 14.3 quarts Displacement - 5.9L V8 Horsepower - 245 HP Torque - 335 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 16.9 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft American Motors Corporation / AMC straight-4 engine / AMC straight-4 engine / AMC 2.5L Oil Capacity - 4.5 quarts Oil Viscosity - 5W-30 Coolant Capacity - 10.0 quarts Displacement - 2.5L I-4 Horsepower - 120 HP Torque - 139 lb/ft Chrysler / Chrysler LA engine / Magnum / 3.9L Magnum V6 Oil Capacity - 4.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 13.7 quarts Displacement - 3.9L V6 Horsepower - 180 HP Torque - 210 lb/ft Chrysler / Chrysler LA engine / Magnum / 5.9L Magnum V8 Oil Capacity - 5.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 14.3 quarts Displacement - 5.9L V8 Horsepower - 245 HP Torque - 335 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 16.9 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft Chrysler / Chrysler LA engine / Magnum / 3.9L Magnum V6 Oil Capacity - 4.5 quarts Oil Viscosity - 5W-30 Coolant Capacity - 13.7 quarts Displacement - 3.9L V6 Horsepower - 180 HP Torque - 210 lb/ft Chrysler / Chrysler LA engine / Magnum / 5.9L Magnum V8 Oil Capacity - 5.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 14.3 quarts Displacement - 5.9L V8 Horsepower - 245 HP Torque - 335 lb/ft Chrysler / Power Tech / 4.7L / 4.7L Magnum V8 Oil Capacity - 6.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 16.9 quarts Displacement - 4.7L V-8 Horsepower - 235 HP Torque - 295 lb/ft American Motors Corporation / AMC straight-4 engine / AMC straight-4 engine / AMC 2.5L Oil Capacity - 4.5 quarts Oil Viscosity - 5W-30 Coolant Capacity - 10.0 quarts Displacement - 2.5L I-4 Horsepower - 120 HP Torque - 139 lb/ft American Motors Corporation / AMC straight-4 engine / AMC straight-4 engine / AMC 2.5L Oil Capacity - 4.5 quarts Oil Viscosity - 5W-30 Coolant Capacity - 10.0 quarts Displacement - 2.5L I-4 Horsepower - 120 HP Torque - 139 lb/ft Chrysler / Chrysler LA engine / Magnum / 3.9L Magnum V6 Oil Capacity - 4.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 13.7 quarts Displacement - 3.9L V6 Horsepower - 180 HP Torque - 210 lb/ft Chrysler / Chrysler LA engine / Magnum / 5.2L Magnum V8 Oil Capacity - 5.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 14.3 quarts Displacement - 5.2L V-8 Horsepower - 230 HP Torque - 295 lb/ft Chrysler / Chrysler LA engine / Magnum / 5.9L Magnum V8 Oil Capacity - 5.0 quarts Oil Viscosity - 5W-30 Coolant Capacity - 14.3 quarts Displacement - 5.9L V8 Horsepower - 245 HP Torque - 335 lb/ft It's no secret that you need regular oil changes to keep your Dodge Dakota engine running smoothly. The recommended change interval is once every 5,000 to 6,000 miles or every 7 to 8 months, whichever comes first. Usually, people take their cars to a service to perform this operation, but you can change the oil on your Dodge Dakota yourself - it only takes half an hour, but it will save you money. To change the oil in the engine of your Dodge Dakota, you will need the following things: engine oil (see the table above for the necessary viscosity and volume), an oil filter, a set of wrenches, air filter, a container for the old oil, and some rag. The oil change order is as follows: Let the engine warm-up: Let the engine run for a few minutes to warm up the oil. This will help the oil flow out of the engine more easily. Don't let the engine run too long - if the oil overheats, you could burn yourself while changing it. 3 to 5 minutes of idling is enough. Locate the oil drain plug: This is typically located on the bottom of the engine. Place the drain pan underneath the plug. Remove the drain plug: Loosen and remove the drain plug using a wrench or socket set. Be careful, as the oil will begin to flow out immediately. Allow the oil to drain: Allow the oil to drain completely into the drain pan. This may take a few minutes. Unscrew the oil filler cap to allow the oil to drain faster. Remove the oil filter: Using a filter wrench, loosen and remove the oil filter. Allow any remaining oil to drain into the drain pan. Replace the oil filter: Install the new oil filter, and lubricate the rubber gasket with fresh oil before tightening it. Install the drain plug: Once the oil has finished draining, reinstall the drain plug and tighten it securely. Add new oil: Using a funnel, add oil to the engine through the oil filler cap. Check the chart above for the correct amount and type of oil to use. Check the oil level: After adding new oil, check the oil level using the dipstick. Add more oil if necessary. We recommend changing your Dodge Dakota air filter whenever you change your oil. Over time, it becomes clogged with dirt, dust, and other debris, negatively affecting engine performance. The process of changing it is straightforward. Find where the air filter is installed in your Dodge Dakota, open the cover, remove the old filter, and install the new one. Close the air filter cover. Start the engine: Let it run for a few minutes, checking for any leaks. Dispose of the old oil: Pour it into a sealable container and take it to a recycling center or automotive service facility that accepts used oil. -no select- 2011 2010 2009 2008 2007 2006 2005 2004 2003 2002 2001 2000 1999 Proven protection for up to 10,000 miles Engineered for use with conventional or synthetic motor oil A special blend of fibers and resin creates a proprietary filter media that captures 95% of dirt particles that... Optimizes engine life for up to 10,000 miles (when used with a full synthetic oil) 99% dirt removal power High-density synthetic blend media Silicone anti-drainback valve that lasts longer than traditional nitrile to protect against... Fit type: Vehicle Specific Package Weight : 1.6 pounds Country of Origin : United States Package Dimensions: 10.16 L x 10.414 H x 10.414 W (centimeters) Proven protection for up to 10,000 miles Engineered for use with conventional or synthetic motor oil A special blend of fibers and resin creates a proprietary filter media that captures 95% of dirt particles that... EFFICIENCY: Tough Guard provides 99% filtration efficiency and ideal protection for drivers who push their vehicles to the extreme. ENGINE PROTECTION: Synthetic fiber/cellulose blend increases dirt-trapping and dirt-holding capacity for higher levels of engine protection... EFFICIENCY: Tough Guard provides 99% filtration efficiency and ideal protection for drivers who push their vehicles to the extreme. ENGINE PROTECTION: Synthetic fiber/cellulose blend increases dirt-trapping and dirt-holding capacity for higher levels of engine protection... Universal Tool - This oil filter removal tool fits oil filters ranging from 60mm to 98mm (Oil filters Range 2-3/8 inch to 3-7/8 inch). A removable 3/8-inch reducer is available for larger clearance and can... Enhanced Leverage - 12" long handle with non-slip red grip ensures extra contact and leverage, making it easier to reach tight spaces. Secure Fit - Lock nuts significantly reduce loosening under vibration and torque, making... Give your F-150 the Perfect Blend of Performance, Protection, and Style from Rough Country. Unmatched Ground Clearance | Premium N3 Shock Absorbers the Best in Performance for On and Off-Road Use. Levels the front with... Tips: Bent Angle Design For Easier Use; Little Oil For Rust Protection High Carbon Steel For Strength And Reliability; Permalock Fastener Eliminates Nut And Bolt Failure Fits Filters From 2-3/8 To 4-1/2 Inches (60 To... Fits Filters from 2 1/2" to 3 1/8". This extra large range enables the 63600 wrench to fit most all import car filters plus the common 3" domestic car filters. Steel jaws grip filter without... [PREMIUM QUALITY]: Industrial grade chrome vanadium steel construction with oil and corrosion resistant black finish provides maximum strength to withstand daily heavy uses and ensure durability [FIT VARIOUS SIZES]: Fits oil filters from 2-3/8 inch... -no select- 2011 2010 2009 2008 2007 2006 2005 2004 2003 2002 2001 2000 1999 ENGINEERED POWER: State-of-the-art air filter media is designed to increase horsepower and acceleration as well as improve overall engine performance RUGGED CONSTRUCTION: K&N Air Filters are manufactured with durable, premium materials and state-of-the-art construction methods... SEE PRODUCT DESCRIPITON FOR FULL LIST OF COMPATIBLE VEHICLES LESS MAINTENANCE: 18,000 mile change interval lasts longer than stock engine air filters at 12,000 miles- our air filters are designed to keep your vehicle on... ENGINEERED POWER: State-of-the-art filtration media provides up to 50% more airflow than disposable paper filters to increase power and acceleration. Clogged or dirty air filters can reduce your vehicle’s acceleration by up to 10%. EASY... ENGINEERED FOR PERFORMANCE – HIGHFLOW air filters maximize the flow of clean air to the engine for optimal performance. Provides up to 50% more air volume than standard paper filters when your engine is under... TRAPS DIRT AND FILTH: Various damaging particles and dust can collect over your engine, however, with FRAM car air filter, Extra Guard entraps these particles for a safer, cleaner, and quality engine performance. DOUBLE MAXIMUM... Meets OE specifications. A clean air filter improves air flow and prevents dirt and dust from entering the engine Follow recommended change intervals as noted in your vehicle owner's manual Designed to enhance the installer's... -no select- 2011 2010 2009 2008 2007 2006 2005 2004 2003 2002 2001 2000 1999 IMPORTANT: Use confirm fitment at top of page to make sure this is the correct plug for your vehicle. - EASY TO INSTALL - Our plug will install in place of your current drain plug.... ★ Quality Material: The magnetic oil drain plug is made of high quality strong stainless steel aluminum and strong magnet, reusable oil drain plug for daily maintenance and oil change. Package contains 1 x size... CHANGE YOUR OIL AT HOME IN 10 MINUTES OR LESS WITH NO MESS. The fastest, easiest, and cleanest way to change your oil at home with the ValvoMax Quick Twist Oil Drain Valve. Replaces your... High-Quality Material: High-strength anode alumina alloy and Permanent Magnet Engine Protection : With Powerful Magnetic Oil Drain Plug, Protect Your Engine From Metal Debris Damage Leak Free: The powerful magnetic oil drain plugs include copper crush washer... ? Engine Protection: This oil drain plug can be a good safegurad of your engine. It can filtrate up fine iron particles, and keep your engine oil clean so as to extend life of your... Proven protection for up to 10,000 miles Engineered for use with conventional or synthetic motor oil A special blend of fibers and resin creates a proprietary filter media that captures 95% of dirt particles that... Engine 0-60 times Horsepower Upgrades Wheels Wheel Interchange Bulbs Dimensions Ground clearance Weight Upgrades Steering wheel Speakers size Upgrades Forgive our ad-diction! It's just our funky little way of keeping the lights on. Bear with us! Home | Forums | Members | Pictures | Contact Us This site is in no way affiliated with Chrysler or any of its subsidiaries. Engine: Engine Code. A sequence of letters and numbers. This includes the engine block type and engine family, but may also include other information.Capacity: Capacity/Filter capacity in litres(liters). Engine oil fill quantity (Service fill).Intervals: Oil Change Intervals (use: normal). Engine oil should be changed at the latest after this time or after miles/km, whichever comes first.The oil filter must be replaced every time the oil is changed, unless the car's owner's manual recommends otherwise. Model: Dodge Ram Dakota, DN (2000 – 2001) (USA / CAN)EngineCapacityIntervalsDakota 2.5 (USA) (DN) (2000 – 2001)(150 ci)4.312 000 km/ 6 monthsDakota 2.5 (USA) (DN) (2001 – 2001)(150 ci)4.312 000 km/ 6 monthsDakota 2.5 4×4 (USA) (DN) (2000 – 2001)(150 ci)4.312 000 km/ 6 monthsDakota 2.5 4×4 (USA) (DN) (2001 – 2001)(150 ci)4.312 000 km/ 6 monthsDakota 3.9 V6 (USA) (DN) (2000 – 2001)238 CID V64.312 000 km/ 6 monthsDakota 3.9 V6 (USA) (DN) (2001 – 2001)238 CID V63.8-4.312 000 km/ 6 monthsDakota 3.9 V6 4×4 (USA) (DN) (2000 – 2001)238 CID V64.312 000 km/ 6 monthsDakota 3.9 V6 4×4 (USA) (DN) (2001 – 2001)238 CID V63.8-4.312 000 km/ 6 monthsDakota 4.7 V8 (USA) (DN) (2000 – 2001)Magnum5.712 000 km/ 6 monthsDakota 4.7 V8 (USA) (DN) (2001 – 2001)Magnum5.712 000 km/ 6 monthsDakota 4.7 V8 4×4 (USA) (DN) (2000 – 2001)Magnum5.712 000 km/ 6 monthsDakota 4.7 V8 4×4 (USA) (DN) (2001 – 2001)Magnum5.712 000 km/ 6 monthsDakota 5.9 V8 (USA) (DN) (2000 – 2001)360 CID V84.712 000 km/ 6 monthsDakota 5.9 V8 (USA) (DN) (2001 – 2001)360 CID V84.712 000 km/ 6 monthsDakota 5.9 V8 4×4 (USA) (DN) (2000 – 2001)360 CID V84.712 000 km/ 6 monthsDakota 5.9 V8 4×4 (USA) (DN) (2001 – 2001)360 CID V84.712 000 km/ 6 monthsModel: Dodge Ram Dakota, ND (2004 – 2010) (USA / CAN)EngineCapacityIntervalsDakota 3.7 V6 (4×2) (USA) (ND) (2005 – 2007)4.710 000 km/ 6 monthsDakota 3.7 V6 (4×4) (USA) (ND) (2005 – 2007)4.710 000 km/ 6 monthsDakota 3.7 V6 (4×2) (CAN) (ND) (2005 – 2007)4.75 000 km/ 3 monthsDakota 3.7 V6 (4×4) (CAN) (ND) (2005 – 2007)4.75 000 km/ 3 monthsDakota 3.7 V6 (4×2) (ND) (2008 – 2010)4.710 000 km/ 6 monthsDakota 3.7 V6 (4×4) (ND) (2008 – 2010)4.710 000 km/ 6 monthsDakota 4.7 V8 (4×2) (USA) (ND) (2005 – 2007)Magnum5.610 000 km/ 6 monthsDakota 4.7 V8 (4×4) (USA) (ND) (2005 – 2007)Magnum5.610 000 km/ 6 monthsDakota 4.7 V8 (4×2) (CAN) (ND) (2005 – 2007)Magnum5.65 000 km/ 3 monthsDakota 4.7 V8 (4×4) (CAN) (ND) (2005 – 2007)Magnum5.65 000 km/ 3 monthsDakota 4.7 V8 (4×2) (USA) (ND) (2008 – 2010)Magnum5.710 000 km/ 6 monthsDakota 4.7 V8 (4×4) (USA) (ND) (2008 – 2010)Magnum5.710 000 km/ 6 months The Dodge Dakota is a mid-size pickup truck that has been known for its versatility and capability. Over the years, it has been equipped with various engine options, each offering unique specifications to cater to different needs. Below is a detailed overview of the engine specifications for the Dodge Dakota across its production years. The Dodge Dakota has featured several engines throughout its production run, including V6 and V8 options. Below is a summary of the most notable engine configurations: Model Year Engine Type Displacement (L) Horsepower (hp) Torque (lb-ft) 1987-1996 3.9L V6 3.9 125-175 200-230 1997-2004 3.7L V6 3.7 210 235 1997-2004 4.7L V8 4.7 230 295 2005-2011 3.7L V6 3.7 210 235 2005-2011 4.7L V8 4.7 302 329 Engine Configuration The engine configuration of the Dodge Dakota varies depending on the model year and specific engine option chosen. Below are the key configurations for the V6 and V8 engines available in the Dakota. V6 Engine Configuration – Type : Naturally aspirated – Number of Cylinders : 6 – Configuration : V-type – Fuel System : Multi-point fuel injection – Bore x Stroke : Varies by year, typically around 3.88 in x 3.31 in – Compression Ratio : Approximately 9.2:1 V8 Engine Configuration – Type : Naturally aspirated – Number of Cylinders : 8 – Configuration : V-type – Fuel System : Multi-point fuel injection – Bore x Stroke : Typically 3.66 in x 3.58 in – Compression Ratio : Approximately 9.5:1 Engine Oil Specifications Proper engine oil is crucial for the longevity and performance of the Dodge Dakota’s engine. The specifications for engine oil vary based on the engine type and model year. Dodge Ram Cummins Engine: Power and ReliabilityRecommended Engine Oil Types – V6 Engines : – Viscosity : 5W-30 or 10W-30 – API Rating : API SL or higher – V8 Engines : – Viscosity : 5W-30 or 10W-30 – API Rating : API SL or higher Oil Capacity – 3.7L V6 : Approximately 5 quarts (with filter) – 4.7L V8 : Approximately 6 quarts (with filter) Service Intervals Regular maintenance is essential for keeping the Dodge Dakota running smoothly. The following service intervals are recommended for oil changes and general maintenance. Oil Change Intervals – Every 3,000 to 5,000 miles : For conventional oil – Every 7,500 to 10,000 miles : For synthetic oil – Every 15,000 miles : – Replace air filter – Inspect brake pads and rotors – Every 30,000 miles : – Replace fuel filter – Inspect and replace spark plugs if necessary – Every 60,000 miles : – Replace timing belt (if applicable) – Inspect coolant and replace if necessary – Every 100,000 miles : – Replace transmission fluid – Inspect and replace differential fluid Conclusion The Dodge Dakota has been a reliable choice for those seeking a mid-size pickup truck with robust engine options. Understanding the engine specifications, configurations, oil requirements, and service intervals is vital for maintaining the performance and longevity of this versatile vehicle. Regular maintenance and the use of the correct engine oil will ensure that your Dakota continues to perform at its best for years to come. OILSfinder > DODGE > Dakota AN 1997-2004 Recommended engine oil, transmission fluids, coolant type, filling capacities and service intervals for DODGE Dakota AN 1997-2004. Aggregate Recommeded fluid Capacity (Liters) Intervals 2,5L petrol engine 10W30 with API certification mark 4,3 5000 km (3000 miles), refer to user or owners manual 2,5L diesel engine 5W40 or 10W40 ACEA B3 or B4 6,8 5000 km (3000 miles), refer to user or owners manual 3,7L gasoline engine (PowerTech) 5W30 or 10W30 with API certification mark 4,7 5000 km (3000 miles), refer to user or owners manual 4,7L gasoline engine (PowerTech) 5W30 or 10W30 with API certification mark 5,7 5000 km (3000 miles), refer to user or owners manual 3,9L petrol engine (Magnum V6) 10W30 with API certification mark 4,3 5000 km (3000 miles), refer to user or owners manual 5,2L and 5,9L petrol engine (Magnum V8) 10W30 with API certification mark 4,7 5000 km (3000 miles), refer to user or owners manual Cooling system (2,5L petrol) MOPAR Antifreeze 5 years/100000 Mile Formula (MS-9769) 9,3 160000 km (100000 miles) or 5 years, whichever comes first Cooling system (2,5L diesel) MOPAR Antifreeze 5 years/100000 Mile Formula (MS-9769) 8,0 160000 km (100000 miles) or 5 years, whichever comes first Cooling system (3,9L) MOPAR Antifreeze 5 years/100000 Mile Formula (MS-9769) 13,2 160000 km (100000 miles) or 5 years, whichever comes first Cooling system (4,7L) MOPAR Antifreeze 5 years/100000 Mile Formula (MS-9769) 16,0 160000 km (100000 miles) or 5 years, whichever comes first Cooling system (5,2L and 5,9L) MOPAR Antifreeze 5 years/100000 Mile Formula (MS-9769) 13,5 160000 km (100000 miles) or 5 years, whichever comes first 4-speed automatic transmission (42RE and 46RE) MOPAR ATF+4 9,5 19000 km (12000 miles) 4-speed automatic transmission (44RE) MOPAR ATF+4 19000 km (12000 miles) 4- and 5-speed automatic transmissions (45RFE and 545RFE) MOPAR ATF+4 13,4 19000 km (12000 miles) 5-speed manual transmission (NV1500HD) Mopar NV1500 lubricant p/n: 4761526 + Friction Modifier 2,2 + 0,1 29000 km (18000 miles) 5-speed manual transmission (NV3500) Mopar NV3500 lubricantp/n: 4874464 2,0 29000 km (18000 miles) 5-speed manual transmission (AX-15) 75W90 API GL-3 or 4 3,1 29000 km (18000 miles) Transfer case (NP231 and NP242) MOPAR ATF+4 1,2 58000 km (36000 miles) Front differential (194) 80W90 API GL-5 1,4 19000 km (12000 miles) Rear differential (8.25) 80W90 API GL-5 2,1 19000 km (12000 miles) Rear differential (8.25 with Trac-Lok) 80W90 or 75W140 (heavy duty) API GL-5 + Friction Modifier 2,1 + 0,120 19000 km (12000 miles) Rear differential (9.25) 75W90 API GL-5 2,3 19000 km (12000 miles) Rear differential (9.25 with Trac-Lok) 75W90 or 75W140 (heavy duty) API GL-5 + Friction Modifier 2,3 + 0,120 19000 km (12000 miles) Power steering Mopar PSF Brakes DOT3 or DOT4 1,0 2 years Fuel (petrol) AKI 87 or 91 / RON 92 or 95 octane 57,0 or 83,0 Information in this table may be incorrect for your region or driving conditions. Refer to the owners/service manual for details. 5/ 5 (1 votes) The 4.7L V8 engine in the Dodge Dakota typically requires 5 quarts of oil for an oil change. This is the standard oil capacity for this engine configuration.Detailed OverviewThe Dodge Dakota is a mid-size pickup truck that was produced by Dodge from 1987 to 2011. One of the engine options available for the Dakota was a 4.7-liter V8 engine. This V8 powerplant had a displacement of 287 cubic inches and produced between 230 to 260 horsepower, depending on the model year.For routine oil changes on a 4.7L V8 Dodge Dakota, the recommended oil capacity is 5 quarts. This includes the oil filter, which holds approximately 1 quart of oil. So the total oil change volume for this engine is 5 quarts.Oil Change Procedure Locate the oil drain plug, usually on the bottom of the oil pan, and drain the old oil. Replace the oil filter. Pour in 5 quarts of new, high-quality motor oil recommended by Dodge for the 4.7L V8 engine. Start the engine and check for any leaks. Allow the engine to run for a few minutes, then check the oil level and top up if necessary.It's important to use the correct oil type and viscosity specified by Dodge for optimal engine performance and longevity. Consult your owner's manual or contact a Dodge dealer for the recommended oil specifications. How much oil does a 4.7 L V8 take?Capacity: 6 quarts (with filter). After refill check oil level.6.5 to 7 quarts is fine.Oil Grade: API*5W-30 (Below 38°C) - SAE 5W-30 is preferred.6 quartsCustomer: how many quarts of oil are needed for a 2005 dodge ram 1500 slt with a 4.7 liter v8 sohc engine? Your vehicle requires 6 quarts or 5.7 liters of oil when changing the oil and filter. The recommended oil is 5w30.SAE 5W30 oil2000-2009 Toyota Tundra 4.7L V8 models use ILSAC GF-5 SAE 5W30 oil type.AMSOIL 5W-30 100% Synthetic High-Mileage Motor Oil.Capacity: 6.6 quarts Initial Fill.It originally produced 235 hp (175 kW) and 295 lb·ft (400 N·m) of torque. The 4.7 L V8 is available with four speed and five speed automatic transmissions and a 5 speed manual transmission.Capacity: 6 quarts (with filter). After refill check oil level.286.7 cu inThe displacement is 4.7 L; 286.7 cu in (4,698 cc) with a bore and a stroke of 3.66 in × 3.405 in (93.0 mm × 86.5 mm). Welcome to our comprehensive guide tailored for your 2004 Dodge Dakota. This guide aims to provide all the essential information for maintaining your Dodge, whether you’re well-versed in car maintenance or just need a quick reference without the vehicle’s manual.3.7L V6 Engine: The 2004 Dodge Dakota equipped with 3.7L V6 Gas engine can take up to 5 quarts of SAE 5W-30 Motor Oil including its oil filter. The compatible OEM Oil Filter for this engine is Mopar 04781452BB ensuring optimal performance.4.7L V8 Engine: The 2004 Dodge Dakota equipped with 4.7L V8 Gas engine has an oil capacity of 6 quarts including its oil filter. The best-suited oil for this engine is SAE 5W-30 Motor Oil. The suggested OEM Oil Filter for this engine is the Mopar 05281090AB, known for its efficiency and compatibility with your Dodge Dakota.Engine Oil for 2004 Dodge DakotaOil Filters for 2004 Dodge Dakota No matter which trim of 2004 Dodge Dakota you own – whether it’s the Base, SLT, Sport – the engine oil requirements remain consistent as long as the engine option is the same. These requirements depend primarily on the engine option your specific trim is equipped with.Quick Recap – 2004 Dodge Dakota Oil Types, Capacities, and FiltersFor 3.7L V6 Engine Oil Capacities: 5 quartsOil Types/Viscosity: SAE 5W-30OEM Oil Filters: Mopar 04781452BBFor 4.7L V8 EngineOil Capacities: 6 quartsOil Types/Viscosity: SAE 5W-30OEM Oil Filters: Mopar 05281090ABMaintain Your Dodge Dakota’s ExcellenceTo ensure peak performance and protect your engine’s health, choose oils and filters that adhere to Dodge’s specifications. Opt for high-quality oil alternatives from reputable brands that meet or exceed Dodge’s standards and are API-certified for gasoline engines. If original OEM oil filters are not available, consider using compatible 2004 Dodge Dakota cross-reference oil filters or alternate Oil Filters from reputable brands.Regular maintenance with the right engine oil and oil change intervals is crucial for the performance and longevity of your 2004 Dodge Dakota. By adhering to these guidelines, you keep your Dodge in prime condition, prepared for any journey ahead. This information is carefully compiled from the specific 2004 Dodge Dakota Owner’s Manual. For more maintenance information, be sure to check out your vehicle’s owner’s manual. © 2022 dodge-specs.comAll Rights Reserved • Privacy Policy